

S6200 Series



外形尺寸(mm)

基本额定载
荷(N) 重量

| select | Inquiry | 型号 | 外形尺寸(mm) | | | | | | r | | 动态(Cr) | 静 态(Cor) | (kg) |
|--------|---------|--------|----------|---------|-------|---------|-------|---------|---------|-----------|--------|-------------|------|
| | | | d(mm) | d(inch) | D(mm) | D(inch) | B(mm) | B(inch) | min(mm) | min(inch) | | | |
| S6200 | 10 | 0.3937 | 30 | 1.1811 | 9 | 0.3543 | 0.6 | 0.0236 | 5110 | 2380 | 0.0320 | | |
| S6201 | 12 | 0.4724 | 32 | 1.2598 | 10 | 0.3937 | 0.6 | 0.0236 | 6180 | 3060 | 0.0370 | | |
| S6202 | 15 | 0.5906 | 35 | 1.3780 | 11 | 0.4331 | 0.6 | 0.0236 | 7450 | 3700 | 0.0450 | | |
| S6203 | 17 | 0.6693 | 40 | 1.5748 | 12 | 0.4724 | 0.6 | 0.0236 | 9560 | 4780 | 0.0650 | | |
| S6204 | 20 | 0.7874 | 47 | 1.8504 | 14 | 0.5512 | 1 | 0.0394 | 12840 | 6650 | 0.1060 | | |
| S6205 | 25 | 0.9843 | 52 | 2.0472 | 15 | 0.5906 | 1 | 0.0394 | 14020 | 7930 | 0.1280 | | |
| S6206 | 30 | 1.1811 | 62 | 2.4409 | 16 | 0.6299 | 1 | 0.0394 | 19460 | 11310 | 0.1990 | | |
| S6207 | 35 | 1.3780 | 72 | 2.8346 | 17 | 0.6693 | 1.1 | 0.0433 | 25670 | 15300 | 0.2880 | | |
| S6208 | 40 | 1.5748 | 80 | 3.1496 | 18 | 0.7087 | 1.1 | 0.0433 | 29520 | 18140 | 0.3660 | | |
| S6209 | 45 | 1.7717 | 85 | 3.3465 | 19 | 0.7480 | 1.1 | 0.0433 | 31500 | 20400 | 0.4200 | | |
| S6210 | 50 | 1.9685 | 90 | 3.5433 | 20 | 0.7874 | 1.1 | 0.0433 | 35000 | 23200 | 0.4590 | | |