


3000A Series



select	Inquiry	Designation	Principal Dimensions(mm)			Basic Load Ratings(KN)		Limited Speed(rpm)	Weight (kg)
			d	D	B	Dynamic(Cr)	Static(Cor)		
3000A	10	26	12	5.5	3.2	18000	23000	0.022	
3200A	10	30	14.3	7.5	4.3	16000	21000	0.05	
3001A	12	28	12	6.1	3.7	17000	22000	0.025	
3201A	12	32	15.9	9	4.9	14000	19000	0.058	
3002A	15	32	13	8.5	5.4	14500	18000	0.036	
3202A	15	35	15.9	10	6	11000	16000	0.066	
3302A	15	42	19	14	8	10000	15000	0.13	
3003A	17	35	14	9	6	12500	16000	0.042	
3203A	17	40	17.5	12.7	7.8	9000	14000	0.096	
3303A	17	47	22.2	17.3	10.4	8000	12000	0.18	
3804A	20	32	10	4.9	3.9	13000	14300	0.02	
3904A	20	37	13	9.3	6.6	12000	13200	0.046	
3004A	20	42	16	14.2	9.6	11000	13000	0.08	
3204A	20	47	20.6	19	12.1	8000	12000	0.16	
3304A	20	52	22.2	19	12.3	8500	12000	0.22	
3805A	25	37	10	5.5	4.9	11500	12700	0.025	
3905A	25	42	13	9.6	7.5	11000	12300	0.062	
3005A	25	47	16	15.2	11	9500	12000	0.1	
3205A	25	52	20.6	20.6	13.9	7500	10000	0.19	
3305A	25	62	25.4	27.6	17.8	7500	10000	0.367	
3806A	30	42	10	5.7	5.6	10000	11500	0.03	

3000A Series

3906A	30	47	13	9.9	8.3	9500	10500	0.095
3006A	30	55	19	20.3	15.5	8000	10000	0.16
3206A	30	62	23.8	25.7	18.5	6300	8500	0.31
3306A	30	72	30.2	37.2	25.9	6000	8000	0.59
3807A	35	47	10	6.1	6.2	8500	10000	0.035
3907A	35	55	15	12.9	11.3	8000	9500	0.138
3007A	35	62	20	24.2	20.4	6500	8500	0.24
3207A	35	72	27	30.4	23.5	5600	7500	0.51
3307A	35	80	34.9	46.1	35.3	5300	7000	0.82