


2200 Series



select	Inquiry	Bearing Designation	Dimension [mm]				Basic load ratings (kN)		Speed ratings (rpm)		Weight (Kg)
			d	D	B	rs min	Cr	Cor	Grease	Oil	
2200	10	30	14	0.6	7.3	1.59	19000	23000	0.047		
2201	12	32	14	0.6	7.6	1.73	17000	20000	0.051		
2202	15	35	14	0.6	7.7	1.85	15000	18000	0.06		
2203	17	40	16	0.6	9.8	2.41	13000	16000	0.088		
2204	20	47	18	1	12.6	3.3	12000	14000	0.14		
2204K	20	47	18	1	12.6	3.3	12000	14000	0.137		
2205	25	52	18	1	12.3	3.45	10000	12000	0.157		
2205K	25	52	18	1	12.3	3.45	10000	12000	0.153		
2206	30	62	20	1	15.2	4.5	8600	10000	0.256		
2206K	30	62	20	1	15.2	4.5	8600	10000	0.25		
2207	35	72	23	1.1	21.5	6.6	7500	8800	0.392		
2207K	35	72	23	1.1	21.5	6.6	7500	8800	0.382		
2208	40	80	23	1.1	22.3	7.35	6700	7900	0.493		
2208K	40	80	23	1.1	22.3	7.35	6700	7900	0.482		
2209	45	85	23	1.1	23.2	8.15	6000	7100	0.54		
2209K	45	85	23	1.1	23.2	8.15	6000	7100	0.528		
2210	50	90	23	1.1	23.2	8.45	5500	6400	0.583		
2210K	50	90	23	1.1	23.2	8.45	5500	6400	0.569		
2211	55	100	25	1.5	26.5	9.9	5000	5800	0.787		
2211K	55	100	25	1.5	26.5	9.9	5000	5800	0.769		
2212	60	110	28	1.5	34	12.6	4600	5400	1.08		

2200 Series

2212K	60	110	28	1.5	34	12.6	4600	5400	1.06
2213	65	120	31	1.5	43.5	16.4	4200	5000	1.44
2213K	65	120	31	1.5	43.5	16.4	4200	5000	1.41
2214	70	125	31	1.5	44	17.1	3900	4600	1.52
2215	75	130	31	1.5	44.5	17.8	3700	4300	1.58
2215K	75	130	31	1.5	44.5	17.8	3700	4300	1.54
2216	80	140	33	2	48.5	19.9	3400	4000	1.99
2216K	80	140	33	2	48.5	19.9	3400	4000	1.95
2217	85	150	36	2	58	23.6	3200	3800	2.54