


RNA Series



select	Inquiry	Bearing Designation			Shaft Diameter [mm]	Weight (Kg)	Boundary Dimensions (mm)					Basic Load Rating (N)		Limiting Speed (rpm) Oil
		Without IR	Weight With IR				d	Fw	D	C	B	Dynamic	Static	
RNA7.8169	-	-	-	7.8	-	7.8	16	-	9	-	-	-	-	-
RNA8X19X9	-	-	-	7.8	-	8	19	-	9	-	-	-	-	-
RNA8X14X8	-	-	-	7.8	-	8	14	-	8	-	-	-	-	-
RNA496	-	-	-	7.8	-	8	15	-	10	-	-	-	-	-
RNA8X15X10TN	-	-	-	7.8	-	8	15	-	10	-	-	-	-	-
RNA4900	24.4	-	-	7.8	-	14	22	-	13	8500	9000	25000	-	-
RNA6900	29.1	-	-	7.8	-	14	22	-	22	12800	15600	25000	-	-
RNA152815	31.7	-	-	7.8	-	15	28	-	15	13600	17200	24000	-	-
RNA4901	16.6	-	-	7.8	-	16	24	-	13	6400	8900	15500	-	-
RNA6901	28.7	-	-	7.8	-	16	24	-	22	14000	18600	15500	-	-
RNA4902	20.5	-	-	7.8	-	20	28	-	13	11000	12900	12000	-	-
RNA6902	35.4	-	-	7.8	-	20	28	-	23	10800	12800	12000	-	-
RNA5902		-	-	7.8	-	20	28	-	18				-	-
RNA4903	20.7	-	-	7.8	-	22	30	-	13	12000	16800	16300	-	-
RNA5903		-	-	7.8	-	22	30	-	18				-	-
RNA6903	39.8	-	-	7.8	-	22	30	-	23	14000	19900	16300	-	-
RNA4904	50.8	-	-	7.8	-	25	37	-	17	11900	16500	15000	-	-
RNA6904	97.7	-	-	7.8	-	25	37	-	30	26000	43000	15000	-	-
RNA22/6 2RS	18	NA22/6 2RS	22	19	6	10	19	12	11.8	5000	4350	18000	-	-
RNA22/6 2RSX	18	NA22/6 2RSX	22	19	6	10	19	12	11.8	5000	4350	18000	-	-
RNA22/8 2RS	29	NA22/8 2RS	34	24	8	12	24	12	11.8	5500	5200	14000	-	-
RNA22/8 2RSX	29	NA22/6 2RSX	34	24	8	12	24	12	11.8	5500	5200	14000	-	-
RNA283833	99.8	-	-	28	-	28	38	-	33	33000	57000	12000	-	-
RNA69/22		-	-	28	-	28	39	-	30				-	-
RNA4905	57	-	-	28	-	30	42	-	17	23600	31500	14000	-	-
RNA6905	106.5	-	-	28	-	30	42	-	30	39000	59000	14000	-	-
RNA305225	-	-	-	28	-	30	52	-	25				-	-
RNA49/28	80	-	-	28	-	32	45	-	17	17400	30000	13000	-	-
RNA69/28	125	-	-	28	-	32	45	-	30	39500	61300	13000	-	-
RNA324527	-	-	-	28	-	32	45	-	27				-	-