


# 62 Series



select Inquiry	Bearing NO.	Shape Dimension								Basic Load Rating(N)		Weight (kg)
		d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic( Cr)	Static( Cor)	
624	4	0.1575	13	0.5118	5	0.1969	0.2	0.0079	1150	400	0.0032	
625	5	0.1969	16	0.6299	5	0.1969	0.3	0.0118	1880	680	0.0051	
626	6	0.2362	19	0.7480	6	0.2362	0.3	0.0118	2800	1060	0.0086	
627	7	0.2756	22	0.8661	7	0.2756	0.3	0.0118	3290	1360	0.0131	
628	8	0.3150	24	0.9449	8	0.3150	0.3	0.0118	3330	1410	0.0170	
629	9	0.3543	26	1.0236	8	0.3150	0.3	0.0118	4160	1780	0.0191	
6200	10	0.3937	30	1.1811	9	0.3543	0.6	0.0236	5110	2380	0.0320	
6201	12	0.4724	32	1.2598	10	0.3937	0.6	0.0236	6180	3060	0.0370	
6202	15	0.5906	35	1.3780	11	0.4331	0.6	0.0236	7450	3700	0.0450	
6203	17	0.6693	40	1.5748	12	0.4724	0.6	0.0236	9560	4780	0.0650	
6204	20	0.7874	47	1.8504	14	0.5512	1	0.0394	12840	6650	0.1060	
6205	25	0.9843	52	2.0472	15	0.5906	1	0.0394	14020	7930	0.1280	
6206	30	1.1811	62	2.4409	16	0.6299	1	0.0394	19460	11310	0.1990	
6207	35	1.3780	72	2.8346	17	0.6693	1.1	0.0433	25670	15300	0.2880	
6208	40	1.5748	80	3.1496	18	0.7087	1.1	0.0433	29520	18140	0.3660	
6209	45	1.7717	85	3.3465	19	0.7480	1.1	0.0433	31500	20400	0.4200	
6210	50	1.9685	90	3.5433	20	0.7874	1.1	0.0433	35000	23200	0.4590	
6211	55	2.1654	100	3.9370	21	0.8268	1.5	0.0591	43500	29300	0.6190	
6212	60	2.3622	110	4.3307	22	0.8661	1.5	0.0591	52500	36000	0.7830	
6213	65	2.5591	120	4.7244	23	0.9055	1.5	0.0591	57500	40000	1.0000	
6214	70	2.7559	125	4.9213	24	0.9449	1.5	0.0591	62000	44000	1.0900	
6215	75	2.9528	130	5.1181	25	0.9843	1.5	0.0591	66000	49500	1.1900	