


## 68 Thin-wall Series



select Inquiry	Bearing NO.	Shape Dimension								Basic Load Rating(N)		Weight (kg)
		d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic( Cr)	Static( Cor)	
684	4	0.1575	9	0.3543	4	0.1575	0.1	0.0039	480	170	0.0010	
685	5	0.1969	11	0.4331	5	0.1969	0.1	0.0059	770	320	0.0019	
686	6	0.2362	13	0.5118	5	0.1969	0.1	0.0059	1080	440	0.0027	
687	7	0.2756	14	0.5512	5	0.1969	0.1	0.0059	1170	510	0.0030	
688	8	0.3150	16	0.6299	5	0.1969	0.2	0.0079	1250	590	0.0038	
689	9	0.3543	17	0.6693	5	0.1969	0.2	0.0079	1330	660	0.0440	
6800	10	0.3937	19	0.7480	5	0.1969	0.3	0.0118	1590	750	0.0050	
6801	12	0.4724	21	0.8268	5	0.1969	0.3	0.0118	1910	1040	0.0060	
6802	15	0.5906	24	0.9449	5	0.1969	0.3	0.0118	2070	1250	0.0070	
6803	17	0.6693	26	1.0236	5	0.1969	0.3	0.0118	2130	1360	0.0080	
6804	20	0.7874	32	1.2598	7	0.2756	0.3	0.0118	3480	2230	0.0190	
6805	25	0.9843	37	1.4567	7	0.2756	0.3	0.0118	3680	2630	0.0220	
6806	30	1.1811	42	1.6535	7	0.2756	0.3	0.0118	4000	3150	0.0260	
6807	35	1.3780	47	1.8504	7	0.2756	0.3	0.0118	4270	3600	0.0290	
6808	40	1.5748	52	2.0472	7	0.2756	0.3	0.0118	4410	3890	0.0330	
6809	45	1.7717	58	2.2835	7	0.2756	0.3	0.0118	4590	4330	0.0400	
6810	50	1.9685	65	2.5591	7	0.2756	0.3	0.0118	6610	6080	0.0520	
6811	55	2.1654	72	2.8346	9	0.3543	0.3	0.0118	8530	8080	0.0830	
6812	60	2.3622	78	3.0709	10	0.3937	0.3	0.0118	9200	8760	0.1060	
6813	65	2.5591	85	3.3465	10	0.3937	0.6	0.0236	10510	9420	0.1250	
6814	70	2.7559	90	3.5433	10	0.3937	0.6	0.0236	10890	10090	0.1350	
6815	75	2.9528	95	3.7402	10	0.3937	0.6	0.0236	11230	10760	0.1450	
6816	80	3.1496	100	3.9370	10	0.3937	0.6	0.0236	11320	11080	0.1550	
6817	85	3.3465	110	4.3307	13	0.5118	1	0.0394	17599	18300	0.2650	
6818	90	3.5433	115	4.5276	13	0.5118	1	0.0394	17853	18961	0.2800	
6819	95	3.7402	120	4.7244	13	0.5118	1	0.0394	18089	19616	0.2980	
6820	100	3.9370	125	4.9213	13	0.5118	1	0.0394	18340	20266	0.3110	