


69 Thin-wall Series



select Inquiry	Bearing NO.	Shape Dimension									Basic Load Rating(N)		Weight (kg)
		d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic(Cr)	Static(Cor)		
694	4	0.1575	11	0.4331	4	0.1575	0.1	0.0059	960	350	0.0017		
695	5	0.1969	13	0.5118	4	0.1575	0.2	0.0079	1070	420	0.0023		
696	6	0.2362	15	0.5906	5	0.1969	0.2	0.0079	1470	600	0.0036		
697	7	0.2756	17	0.6693	5	0.1969	0.3	0.0118	1600	710	0.0050		
698	8	0.3150	19	0.7480	6	0.2362	0.3	0.0118	2230	910	0.0076		
699	9	0.3543	20	0.7874	6	0.2362	0.3	0.0118	2480	1090	0.0085		
6900	10	0.3937	22	0.8661	6	0.2362	0.3	0.0118	2690	1270	0.0100		
6901	12	0.4724	24	0.9449	6	0.2362	0.3	0.0118	2890	1460	0.0120		
6902	15	0.5906	28	1.1024	7	0.2756	0.3	0.0118	4320	2250	0.0180		
6903	17	0.6693	30	1.1811	7	0.2756	0.3	0.0118	4590	2550	0.0190		
6904	20	0.7874	37	1.4567	9	0.3543	0.3	0.0118	6370	3680	0.0380		
6905	25	0.9843	42	1.6535	9	0.3543	0.3	0.0118	6660	4180	0.0440		
6906	30	1.1811	47	1.8504	9	0.3543	0.3	0.0118	7240	5010	0.0500		
6907	35	1.3780	55	2.1654	10	0.3937	0.6	0.0236	10390	7160	0.7500		
6908	40	1.5748	62	2.4409	12	0.4724	0.6	0.0236	13020	9200	0.1180		
6909	45	1.7717	68	2.6772	12	0.4724	0.6	0.0236	13490	10130	0.1280		
6910	50	1.9685	72	2.8346	12	0.4724	0.6	0.0236	13900	10990	0.1330		
6911	55	2.1654	80	3.1496	13	0.5118	1	0.0394	14820	12690	0.1770		
6912	60	2.3622	85	3.3465	13	0.5118	1	0.0394	15080	13480	0.1910		
6913	65	2.5591	90	3.5433	13	0.5118	1	0.0394	19950	17490	0.2000		
6914	70	2.7559	100	3.9370	16	0.6299	1	0.0394	25950	31850	0.3270		
6915	75	2.9528	105	4.1339	16	0.6299	1	0.0394	26780	23560	0.3450		
6916	80	3.1496	110	4.3307	16	0.6299	1	0.0394	27590	25280	0.3630		
6917	85	3.3465	120	4.7244	18	0.7087	1.1	0.0433	31900	29700	0.5170		
6918	90	3.5433	125	4.9213	18	0.7087	1.1	0.0433	32800	31500	0.5400		
6919	95	3.7402	130	5.1181	18	0.7087	1.1	0.0433	33700	33300	0.5670		
6920	100	3.9370	140	5.5118	20	0.7874	1.1	0.0433	39901	39135	0.7710		