


Jaw Coupling



select	Inquiry	Type	D	L	d1~d2	l1	l2	M	Tightening bolts Center to shaft end Distance G	Center to Axis Distance F	Tightening torque (N * m)	Rated torque (N * m)	Maximum torque (N * m)	Maximum speed (rpm)	Moment of inertia (kg * m2)	Radial deviation (mm)	Angular deviation (°)	Axial deviation (mm)
LM-14*22	14	22	3~8	8	6	M3	4	顶 丝 型	1	1.10	2.20	19000	46	0.02	1	0.60		
LM-20*25	20	25	4~10	7.50	10	M3	3.75	7	1.30	2.80	5.60	17000	55	0.02	1	0.60		
LM-20*30	20	30	4~10	10	10	M3	5	7	1.30	2.80	5.60	17000	55	0.02	1	0.60		
LM-25*30	25	30	4~12	9.50	11	M3	5	8	1.50	6	12	16000	63	0.02	1	0.60		
LM-25*35	25	35	4~12	12	11	M3	6.25	8	1.50	6	12	16000	63	0.02	1	0.60		
LM-30*35	30	35	5~16	11.50	12	M4	5.75	11	1.70	6.50	13	15000	72	0.02	1	0.60		
LM-30*42	30	42	5~16	15	12	M4	5	11	1.70	6.50	13	15000	72	0.02	1	0.60		
LM-35*50	35	50	8~19	18.50	13	M4	5.50	13	2.80	16	32	14000	200	0.02	1	0.80		
LM-40*40	40	40	6~22	12.50	15	M5	8.75	15	4	32	64	13000	450	0.02	1	0.80		
LM-40*45	40	45	6~22	12.5/17.5	15	M5	8.50	15	4	32	64	13000	500	0.02	1	0.80		
LM-40*50	40	50	6~22	17.50	15	M5	8.75	15	4	32	64	13000	450	0.02	1	0.80		
LM-40*55	40	55	6~22	20	15	M5	8.50	15	4	32	64	13000	500	0.02	1	0.80		
LM-40*66	40	66	6~22	25.50	15	M5	8	15	4	32	64	13000	550	0.02	1	0.80		
LM-40*75	40	75	14~22	25.5/35	15	M5	8	15	4	32	64	13000	575	0.02	1	0.80		
LM-40*85	40	85	14~22	35	15	M5	8	15	4	32	64	13000	600	0.02	1	0.80		
LM-45*55	45	55	8~25	20	15	M6	10	17	4	40	80	12000	750	0.02	1	0.80		
LM-45*66	45	66	8~25	25.50	15	M6	8.50	17	4	40	80	12000	800	0.02	1	0.80		
LM-45*75	45	75	14~25	25.5/35	15	M6	8.5 /10	17	4	40	80	12000	850	0.02	1	0.80		
LM-45*85	45	85	14~25	35	15	M6	10	17	4	40	80	12000	850	0.02	1	0.80		
LM-55*66	55	66	12~30	25	16	M8	9.50	21	4	46	92	10500	1400	0.02	1	0.80		
LM-55*78	55	78	12~30	31	16	M8	10.50	21	4	46	92	10500	1500	0.02	1	0.80		
LM-55*95	55	95	14~28	39	17	M8	11.50	21	4	46	92	10500	1550	0.02	1	0.80		
LM-55*110	55	110	14~28	47	16	M8	12.50	21	4	46	92	10500	1600	0.02	1	0.80		
LM-65*80	65	80	14~38	31	18	M8	12	27	15	109	218	8300	2800	0.02	1	0.80		
LM-65*85	65	85	14~38	31/36	18	M8	12	27	15	109	218	8300	2800	0.02	1	0.80		
LM-65*90	65	90	14~38	36	18	M8	12	27	15	109	218	8300	2800	0.02	1	0.80		
LM-80*90	80	90	14~45	34	22	M10	13.50	30	15	135	270	7000	3500	0.02	1	1		
LM-80*102	80	102	14~45	34/46	22	M10	13.50	30	15	135	270	7000	3500	0.02	1	1		
LM-80*114	80	114	14~45	46	22	M10	13.50	30	15	135	270	7000	3500	0.02	1	1		
LM-95*126	95	126	18~55	51	24	M12	16.50	34	15	260	520	6000	4600	0.02	1	1		